Axiomatic Semantics

The guarded command language

Semantics

- A programming language specification consists of a syntactic description and a semantic description.
- **Syntactic description**:symbols we can use in a language
- **Semantic Description**: what phrases in a programming language mean.
- Semantics may be given as
  - Denotational
  - Axiomatic
  - Operational
- Here we concentrate on axiomatic descriptions: the meaning is defined by a logical calculus called **program logic** which provides a tool for the derivation of programs and assertions of the form {Q} p {R}

Example:

- Read in 2 integers and output their product divided by their sum. You are guaranteed that there are 2 integer values in the input stream.
- Precondition = { Input stream contains two integer values}
- Postcondition = { Product / Sum is output}

- {Q} p {R} states that a program p. once started in a state satisfying {Q} will lead to a situation characterised by{R}

- {Q} may also be written as the weakest precondition of p tp achieve postcondition R i.e. wp(p, R)

- Wp(S, R) represents the set of all states such that execution of S beginning in any one of them is guaranteed to terminate in a finite amount of time satisfying R.
- **Examples:**
  - wp (i = i +1, i <= 1)
  - S: if x>=y then z = x else z = y, R: z = max(x,y) calculate wp(S,R)
  - Let S be as above and R: z=y, calculate wp(S,R)
  - S: if x>=y then z = x else z = y,R: z = y-1 calculate wp(S,R)
  - Let S be as above, R: z= y+1

- Command S is usually designed to establish the truth of a postcondition R. We may not be interested in wp(S,R). If we can find a stronger precondition Q that represents a subset of the set wp(S,R)and can show Q => wp(S,R) then we are content with Q as the postcondition.

- When we write {Q} p {R} we denote Total Correctness
- Q {p} R denotes partial correctness.

Some properties of wp

- Law of excluded miracle: wp(S,F) = F
- Distributivity of conjunction: wp(S,Q) $\wedge$wp(S,R) = wp(S,Q $\wedge$R)
- Law of monotonicity: if Q => R then wp(S,Q) => wp(S,R)
- Distributivity of disjunction: wp(S,Q) $\vee$wp(S,R) => wp(S,Q $\vee$ R)

- **Nondeterministic:**
  - Execution of a command is nondeterministic if it need not always be exactly the same each time it is begun in the same state
  - e.g. {x = 4} x := 14 || x := x+1 {?}

Exercises

- Determine
  - wp (i:= i +1, i >0)
  - wp(i = i +2; j = j -2, i + j = 0)
  - wp(i = i +1;j = j -1, i *j = 0)
  - wp(z = z*j; i :=i -1, z * j^i = c)
  - wp(a[i] = 1, a[i] = a[j])
  - wp(a[a[i]] = i, a[i]=i)

Skip & Abort

- Skip
  - Execution of the skip command does nothing.
  - It is equivalent to the empty command;
  - It is the identity transformer
  - wp(skip, R) = R
- Abort
  - wp(abort, R) = False
  - Abort should never be executed as it may only be executed in a state satisfying False.

Sequential Composition

- A way of composing larger programs from smaller segments
- If s1 and S2 are commands then s1;s2 is a new command
- wp (s1;s2, R) = wp(s1, wp(s2, R))

Assignment

- **x := e**
- x is a simple variable, e is an expression and the types of x and e are the same
- wp(x := e, R) = domain(e) cand R_e^x
- Domain(e) is a predicate that describes the set of all states in which e may be evaluated i.e. is well defined.
- Usually we write: wp(x := e, R) = R_e^x

Examples:

- wp(x:=5, x =5)
- wp(x:=5, x !=5)
- wp(x:=x+1, x <10)
- wp(x:= x*x, x^4 =10)
- wp(x:=a/b, p(x))
- wp(x:=b[i], x=b[i]) for b, an array with indexes 0 ..100

Multiple Assignment

- Multiple assignment has the form

  x1, x2, x3, …, xn := e1, e2, e3, …, en

  where xi are distinct simple variables and ei are expressions.
- **Definition:**

  wp(x1, x2, x3, …, xn := e1, e2, e3, …, en, R)

  = domain(e1, e2, e3, …, en) cand $R_{e1, e2, e3, \ldots, en}^{x1, x2, x3, \ldots, xn}$

Examples: x,y := y, x;

x,y,z := y,z,x

wp(z,y:=z*x, y-1, y>=0 ∧ z*x^y = c)

- Execution of an expression may change only the variables indicated and evaluation of an expression may change no variables.
- This prohibits functions with side effects and allows us to consider expressions as conventional mathematical entities I.e. we can use associativity, commutativity of addition etc.
- Example: Swapping two variables:
- wp(t:=x; x:=y; y:=t, x = X ∧ y = Y}

The if statement

If $B_1 \rightarrow S_1$
[] $B_2 \rightarrow S_2$
… [] $B_n \rightarrow S_n$
fi

- Each $B_i \rightarrow S_i$ is a guarded command and each S_i may be any command e.g. skip, about, sequential composition etc.
- If any guard B_i is not well defined in the state in which execution begins, abortion may occur. This is because nothing is assumed by the order of evaluation of the guards.
- At least one guard must be true to avoid abortion.
- If at least one guard B_i is true, then 1 guarded command $B_i \rightarrow S_i$ is chosen and S_i is executed.

Wp (If, R)

Wp (If, R) =
domain(**BB**) $\wedge$ **BB** $\wedge$ ($B_1 \Rightarrow$ wp(S_1, R)) $\wedge$ … $\wedge$ ($B_n \Rightarrow$ wp(S_n, R))
where **BB** = $B_1 \vee B_2 \vee \ldots \vee B_n$
$\equiv$

wp(If, R) = ($\exists$i : 1 <= i <= n : B_i) $\wedge$ ($\forall$i : 1 <= i <= n : $B_i \Rightarrow$ wp(S_i, R))

Example: A $\equiv$ (**if x >=0 $\rightarrow$ z := x**
[] x <= 0 $\rightarrow$ z := -x)

wp(A, z = abs(x)) = True

Example:

{T} $\equiv$ { (x>=0) $\vee$ (x <= 0)}
if x >= 0
{x = abs(x)}
z:=x;
{z = abs(x)}
[] x >= 0
{- x = abs(x)}
z:= - x;
{z = abs(x)}
fi
{ (x >=0 $\vee$ x <= 0) $\wedge$ (x >=0 $\wedge$ z = abs(x)) $\vee$ (x <=0 $\wedge$ z = abs(x)) }
$\equiv$ {z = abs(x)}

Exercises:

- Complete and Simplify:

1. wp (**S**, a>0 $\wedge$ b >0) where
S = if a > b $\rightarrow$ a:= a-b
[] b > a$\rightarrow$ b:= b-a
fi

2. wp(S, x <= y) where
S = if x > y $\rightarrow$ x,y :=y,x
[] x<=y $\rightarrow$ skip
fi

The Iterative Command

- Do B $\rightarrow$ S oD
  - where B $\rightarrow$ S is a guarded command. This is equivalent to a while loop.
  - Do (x>=0) $\rightarrow$ x:= x-1 oD
    $\equiv$ while (x>=0) { x := x-1}

We can generalize in the guarded command language to:
Do B1 $\rightarrow$ S1
[] B2 $\rightarrow$ S2
…
[] Bn $\rightarrow$ Sn
oD where n>=0, and Bi $\rightarrow$ Si is a guarded command.
Note: Non Determinism is allowed.

- Let BB = B1 $\vee$ B2 $\vee$ … $\vee$ Bn
- **H_0(R) = $\neg$BB $\wedge$ R**
  - Represents the set of states in which execution of DO terminates in 0 iterations with R true, as the guards are initially false

- **wp(DO,R) = $\exists$k: 0<=k: H_k(R)**
  - Represents the set of states in which execution of DO terminates in a bounded number of iterations with R true.

Example: What does the following calculate? How can we prove it?
i,s = 1, b[0];
Do i <> 11 $\rightarrow$ i,s := i+1, s + b[i] **OD**
{R: s = Σ k: 0<=k<11:b[k])}

- **Invariant {P}** : Predicate that is true throughout the program
- **Guard Bi, BB:**
  - True on entry into the loop
  - May be true or false at the exit point of the loop => re-evaluate guard
  - The guard is always false after the loop terminates
  - **Postcondition {R}:** The postcondition should imply the Invariant and the negation of the guard i.e. **P ∧ ¬BB => R**
  - **Precondition{Q}:** Should imply the Invariant with initialisations.

Loop Template

{Q} ⇒ {P}

Do BB

{P ∧ BB}

"Loop Body"

{P}

Od

{P ∧ ¬BB} ⇒ {R}

Program Verification

- Given a precondition, a postcondition and some code verify that the code when executed in a state satisfying the given precondition achieves the given postcondition.

{Q} : **{Array b has values}**

i,s:= 1,b[0]

Do i <> N

  i,s := i +1, s+b[i];

Od

{R}: **{s = Σ k: 0<=k<11:b[k])}**

Loop Termination

- To show that a loop terminates we introduce an integer function, **t**. where **t** is a function of the program variables i.e. an upper bound on the number of iterations still to be performed.
- **t** is called the **variant function** and it is a measure of the amount of work yet to be completed by the loop.
- Each iteration of the loop decreases **t** by at least one
- As long as execution of the loop has not terminated then **t** is bounded below by 0. Hence the loop must terminate.
- In our last example t: 11-i

Checklist for loops

- Show that **P** is true before the execution of a loop begins
- Show that **P ∧ ¬BB ⇒ R** i.e. when the loop terminates the desired result is true.
- Show that **{P ∧ Bi} Si {P}** 1<=i<=n i.e. execution of each guarded command terminates with P true so that P is an invariant of the loop.
- Show that **P ∧ BB ⇒ (t >0)** so that the bound function i.e. "the amount of work yet to be done" is bounded from below as long as the loop has not terminated.
- Show that **{P ∧ Bi} t1 :=t;Si; {t<t1}** for 1 <=i<=n so that each loop iteration is guaranteed to decrease the bound function. In general **t** can only provide an upper bound on the number of iterations to be performed. Hence, it is called the bound function or the variant function.